



TECHNICAL RIDER

Backline requirements (when NOT supplied by the band):

BASS RIG: 2 x 4x10 Gallien Krueger 700 RBII

Alternatives:

- AMPEG SVT4/SVT7
- Any 400W compatible with at least 1 4x10 Cabinet

GUITAR RIGS (2 of them): PEAVEY 6505 / PEAVEY JSX

Alternatives:

- JCM 2000 DSL
- JCM 900 LEAD
- *. Each rig at least 1 Marshall cabinet 4x12

DRUMS: Any TAMA drum kit with relatively new skins, not necessarily brand new, but in tuneable condition (no rattling at low tuning)

- 22" Kick Drum with the mic hole
- 12" Rack Tom
- 14" Floor Tom
- 16" Floor Tom

All double braced Hardware:

- Snare stand
- Hi-Hat stand with clutch
- 4 Cymbal stands (not necessarily boom stands unless rack tom mount on them)
- Drum stool
- Drum mat (carpet)

1 clean towel and 4 small bottles of water room temperature

IMPORTANT!!!

- Batter skin on the kick drum MUST have a double patch in the centre.
- If rack tom is deeper than 10" please provide one more snare stand (2 in total)
- If there's no chance of getting a TAMA kit, anything else will do. Please NO DW!!!
- Each cymbal stand MUST have a full set of cymbal protection inc. plastic or rubber holding bit, at least two felts and a nut
- Drum mat (carpet) is a must.

Drum Microphones and stands:

Beta 52 or D112 or SM91 plus short boom stand

SM57 plus short boom stand – Snare top

SM81 or KM184 plus short boom stand – Hi-Hat

604 or 421 plus clips or boom stand x3 - Toms

AKG214 or SM81 plus tall boom stand x2 – Overheads

VOCALS: 2 Mics in the front of the stage, Artist to supply floor mounted TC Helicon Voicelive vocal processor

